

N0.	SERIES	CODE	COLORS	SIZE	THICKNESS
1	Carbon Fiber PPF	6D01B-P	1	60 " x 50ft / 1520mm x 15m	7.5mil
Structure					
PET Protection Layer					2mil
Top Coating Layer (Cashew ®)					7µm (0.3mil)
TPU Color Layer (Lubrizol ®)					113µm (4.45mil)
Based Layer (Lubrizol ®)					40µm (1.57mil)
Adhesive Layer (Ashland ®)					30µm (1.18mil)
PET Release Liner					2mil
Specifications					
Finish	Gloss				
Application Way	Wet				
Warranty	5 Years				
Warranty Coverage	Yellowing ;Staining; Cracking ;Blistering ;Delaminating; Fading				
Gloss	>90 GU				
Release Force	≤0.3 (N/25mm)				
Initial tack	≥8 (N/25mm)				
24h/180°Peeling Force	≥12 (N/25mm)				
Storage Aging Peeling Force	≥10 (N/25mm)				
Apply Aging Peel Force	≥16 (N/25mm)				
Tensile Strength	45 MPa				
Elongation At Break	≥120%				
Maximum Temperature	110≥5min				
Storage Period	2 Years from the Manufactured Date in Temperature Range of +10°C to +25°C Relative Humidity 50%, in original package, away from direct sunlight, clean and dry place .				