

N0.	SERIES	CODE	COLORS	SIZE	THICKNESS
1	Gloss Aluminum PPF	GAF-P	25	60 " x 50ft / 1520mm x 15m	7mil ± 0.5
2	Pearl PPF	GPF-P	3	60 " x 50ft / 1520mm x 15m	7mil ± 0.5
3	Gloss PPF	HGF-P	61	60 " x 50ft / 1520mm x 15m	7mil ± 0.5
4	Gloss Metallic PPF	HGM-P	11	60 " x 50ft / 1520mm x 15m	6.5mil ± 0.5
5	Pearl Diamond PPF	MDF-P	35	60 " x 50ft / 1520mm x 15m	7mil ± 0.5
6	Glossy Copper Metallic PPF	SCM-P	1	60 " x 50ft / 1520mm x 15m	7mil ± 0.5

Structure

PET Protection Layer	2mil
Top Coating Layer (Cashew ®)	7µm (0.3mil)
TPU Color Layer (Lubrizol ®)	100µm (3.95mil ± 0.5)
Based Layer (Lubrizol ®)	40µm (1.57mil)
Adhesive Layer (Ashland ®)	30µm (1.18mil)
PET Release Liner	2mil

Specifications

Finish	Gloss
Application Way	Wet
Warranty	5 Years
Warranty Coverage	Yellowing ;Staining; Cracking ;Blistering ;Delaminating ; Fading
Gloss	>90 GU
Release Force	≤0.3 (N/25mm
Initial tack	≥8 (N/25mm)
24h/180°Peeling Force	≥12 (N/25mm)
Storage Aging Peeling Force	≥10 (N/25mm)
Apply Aging Peel Force	≥16 (N/25mm)
Tensile Strength	45 MPa
Elongation At Break	≥120%
Maximum Temperature	110≥5min

Storage Period 2 Years from the Manufactured Date in Temperature Range of +10°C to +25°C Relative Humidity 50%, in original package, away from direct sunlight, clean and dry place .